



The Brighter Choice



STERLING
CRI >90

Clearer. Brighter. Sharper.



Delivering Increased Colour Accuracy with CRI>90

For environments where true colour enhances wellbeing, precision, and presentation.

The STERLING panel can now deliver excellent colour-rendering with the addition of CRI>90 versions, available in 4000K and 5000K CCT options.

A CRI>90 ensures colours are revealed as true as under natural daylight, making it perfect for environments where colour accuracy is critical – from healthcare facilities and retail spaces to offices & corridors.

CRI>80




CRI>90

Ideal Applications



Healthcare & clinical facilities



Retail environments



Offices & corridors



Education facilities

STERLING CRI>90

Built for Installers & Contractors

- **Multiple mounting options** – one panel suits recessed, surface and suspended setups
- **Plug-in emergency packs** – tool-free maintenance, easy access
- **Remote driver with loop-in/loop-out** – speeds up wiring and testing
- **7-year warranty** – includes lithium emergency battery as standard
- **From first fix to final sign-off, STERLING is designed to make life easier on site.**

Features & Benefits

- **Superior Colour Accuracy** – show colours vividly and accurately
- **Edge-lit design** – ultra-thin profile, even light distribution
- **Opal diffuser or UGR<19 micro-prismatic cover** – glare control for professional schemes
- **IP44 rated & TP(a) fire-rated** – safe for wet and integrated ceiling applications
- **ENEC-approved, flicker-free driver** – reliable, comfortable light with no strobing



Standard with UGR<19 microprismatic controller in 4000K or 5000K, CRI>90


ORDER CODE	DIMENSIONS		POWER (W)	LUMENS (lm)	EFFICACY (Llm/c.W)	OPTICS	DIMMING	CRI	CCT (K)
	WIDTH	LENGTH							
NST/UGR19/66/940	595	595	25	3274	134	UGR<19		>90	4000
NST/UGR19/66/950	595	595	25	3147	128	UGR<19		>90	5000

Standard Digital Dimming (DD) with UGR<19 microprismatic controller in 4000K or 5000K, CRI>90


ORDER CODE	DIMENSIONS		POWER (W)	LUMENS (lm)	EFFICACY (Llm/c.W)	OPTICS	DIMMING	CRI	CCT (K)
	WIDTH	LENGTH							
NST/UGR19/66/DD/940	595	595	25	3274	134	UGR<19	Digital Dimming	>90	4000
NST/UGR19/66/DD/950	595	595	25	3147	128	UGR<19	Digital Dimming	>90	5000



OPAL DIFFUSER



UGR<19 MICROPRISMATIC CONTROLLER



OPTIONS:

- Low output 19W (Suffix LO)
- High output 37W (Suffix HO)



SMART CONTROLS WITH HUBSENSE

HubSense is the most functional, flexible and open smart wireless lighting control system available today. Our fitting can be supplied with HubSense installed, ready to deliver even greater energy savings, sophisticated control and full remote emergency test and monitoring.

Contact our technical team for details - technical@nvcuk.com

FOR FULL
STERLING RANGE
SCAN QR CODE



NVC LIGHTING LTD

NVC Park 201, Hollymoor Way, Rubery, Birmingham, B31 5HE UK

+44 (0)121 457 6340 | sales@nvcuk.com | www.nvcuk.com

